RP285A1 APEX ROPE WRENCH

Product Datasheet

Patent Pending. Made in Wales, UK

PRODUCT OVERVIEW

The ISC APEX is fitted with a swing-open side frame which allows for quick and easy mid-line attachment, even when wearing gloves! The push-button, swing-open side frame has a double-lock closure system for added security and an audible 'click' to confirm closure.

The ISC APEX is fitted with an adjustable cam, allowing the user to select from multiple, clearly identifiable friction settings, in accordance with rope type and diameter. The spring-loaded cam can be adjusted in less than 5 seconds- simply depress the spring-loaded button, swing the side plate open and then pull the spring -loaded cam outwards a short way. Rotate the cam to select the new setting, release the cam and close the device! No tools needed and no drop-able parts!

The ISC APEX also allows the user to change the tether without having to alter the friction setting.

TECHNICAL INFORMATION

Part Code	RP285A1
Rope ø	11-13mm (7/16-1/2")
Adjustable Friction Settings	As standard
Mid-line Attachable	As standard. Push-button swing frame, with double-lock closure (no droppable parts)
Compatibility	Squirrel FLEX Tether (and other ISC Tethers)
Dimensions	98 x 47 x 32mm (3.85 x 1.85 x 1.25")
WLL	120kg (264lb)
Weight	177g (6.2oz)
Material/finish	Aluminium, Anodised Frames, Stainless Steel cam & bollard
Standards	NOT for PRIMARY LIFE SUPPORT

I|S|C Solutions in Metal

+44 (0) 1248 363 110 **www.iscwales.com** sales@iscwales.com

Unit 1, Plot 2, Llandygai Industrial Estate
Bangor, Gwynedd, LL57 4YH, United Kingdom
Company Registered in England & Wales, No. 2999156

climb. work. rescue.

Manufactured in Wales, UNITED KINGDOM