WIRECORE FLIPLINE WITH ADJUSTER

Adjustable in length, this assembly already comes integrated and is UKCA and CE certified. The rope grab allows climbers to modify the rope length. This Flipline comes with three different termination options.



APPLICATIONS:

Work positioning

MATERIAL COVER: CORE:

Polyester Galvanised wire

TEST STANDARDS:

UKCA and CE EN 358 certified

PROPERTIES:

Galvanised 7x19 wire provides zero stretch, cut resistant and gives ideal balance of flexibility and weight for improved flip performance. 16 plait

Polyester cover for excellent abrasion resistance and

provides grip against the tree.

Fitted with ISC RP203 rope grab to provide length

adjustment.

COLOURS:

Colours may vary



TERMINATIONS

Available with plain ends, fixed or swivel snaphook and finished with a stopper the other end.



STOPPER TERMINATION

PERFORMANCE

DIAMETER	LENGTH	UNIT WEIGHT (ROPE +GRAB)	MINIMUM BREAK LOAD	MAX. USER WEIGHT
mm	m	g	kN	kg
13	2	823	15	140
13	3	1041	15	140
13	4	1259	15	140
13	5	1477	15	140

Ropemaker Park Hailsham East Sussex, BN27 3GU England

Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360 USA

UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com



Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability

and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.

Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.