

Marlow [®] DATASHEET

DRACO

Specially developed for the most demanding arborist rigging applications, the Draco's proven 16 plait cover is married with a braided high tenacity core to give a tough but high strength lowering line.

The fully braided construction prevents twisting and allows for a supple rope without compromising on durability. The core/ cover polyester construction ensures performance, durability and economy from a single rope.



PERFORMANCE

DIAMETER	CIRCUMFERENCE	MASS		AVERAGE STRENGTH			MIN STRENGTH		
		mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg
12	1/2	100.6	6.75	3910	8620	38.4	3590	7914	35.22
14	9/16	130.4	8.74	5596	12337	54.9	5036	11102	49.40
16	5/8	197.0	13.21	8350	18408	81.9	7550	16645	74.07

Key Specifications:

- Material:** Polyester
- Construction:** 16 plait, braided -12 (12mm or 16mm) strand
- Colour:** 12mm (blue fleck), 14mm (green fleck), 16 (red fleck)
- Features:**
- Hardwearing cover for increased life in tough environments.
 - UV resistant polyester construction for outdoor use.
 - Braided from high tenacity polyester to give high strength, low stretch, and some capacity to absorb dynamic loads.
 - Fully torque balanced construction to eliminate twist and aid handling.
 - Supple Braid, runs well on sheaves and holds knots well.
 - Spliceable to create high strength termination.

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

Certificate Number 315
ISO 9001
ISO 14001