DATASHEET ®

TYPHOON (

Marlow Typhoon is stirring up a storm and continues the trend of development and innovation for the modern Arborist. Typhoon has been developed with low stretch and toughness in mind made with high-tenacity Polyester, Typhoon has a 16-plait polyester cover and multiple Polyester twisted core, making it a perfect partner for most modern hardware.

Being 12.2 mm in diameter Typhoon is perfectly suited for Arborists wishing to move from the more traditional larger heavier diameter climbing lines, but still wishing to retrain the benefits of very low stretch and a diameter that is easy to handle together low profile spliced eye this makes Typhoon a worthy addition to the range.

Certified to EN 1891 Type A, with low Profile Eye and Whipp

REVOLUTIONISING MODERN CLIMBING

ROPE PROPERTIES	MEASUREMENT
DIAMETER	12.2 mm
WEIGHT	110 g/m
CORE WEIGHT	34 g/m
COVER WEIGHT	76 g/m
ELONGATION	*1.5%
STATIC STRENGTH	32.8kN
STRENGTH FIG 8	19.1 kN
STRENGTH SPLICED	22.9 kN
IMPACT FORCE	5.6kN
DROPS	5+

*Elongation from 50kg to 150kg load, as tested according to EN 1891



Key Specifications:

Material: Polyester

Lengths: 25m, 35m, 45m, 60m

Colour: Red with yellow and Yellow with Red
Features: Light weight, low stretch and easy to handle

Terminations: Low profile splice finished with a whip

Marlow Ropes Ltd Ropemaker Park Hailsham East Sussex, BN27 3GU England Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360 USA UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com







Certificate Number 315 ISO 9001 ISO 14001